



TRITON

Petroleum Resin Based Sealer

GENERAL DESCRIPTION

Triton® utilizes a special petroleum resin-based tar combined with specialty minerals, polymer additives, and emulsifiers to deliver exceptional performance. It cures to a rich black color that protects and lasts for seasons to come. Triton® forms a tough and durable coating that shields asphalt from the damaging effects of weather and traffic. IT is a low-VOC product that provides superior durability and fuel resistance compared to asphalt-based sealers, without the strong odor or irritation associated with refined tar sealers.

RECOMMENDED USES

Triton® is suitable for all types of asphalt pavements including:

- Home driveways.
- Commercial parking lots.
- Apartment complexes.
- Restaurants.
- Schools.
- Gas stations.
- Truck terminals.
- Airfields, taxiways, and airport shoulders.

MIX DESIGN RECOMMENDATIONS

Important - All mix designs must include clean, quartz, angular sand.

- **Triton® Conc.:** 100 Gal.
- **Potable Water:** 20-30 Gal.
- **Sand 40/20 or 70/20:** 200-500 Lbs.

**The use of an additive is optional, we carry the STAR line of additives that are all compatible.*

WEATHER LIMITATIONS

- Surface and air temperature must be at least 50F and rising.
- Do not apply on rainy, foggy, or extremely humid days, or when rain is expected within 24 hours.
- If pavement temperature exceeds 100F, lightly mist the surface with water to aid application. Do not allow water to puddle.

APPLICATION TOOLS

- Use conventional tools, Brush, rubber squeegee or spray rig.
 - Clean up with water.
 - Dried sealer on tools - Will require mechanical removal (wire brushes and scrapers).

CURING TIME

Cure times depend on temperature, humidity, and sun light:

- Lower temperatures, high humidity, or lack of direct sunlight will prolong curing.
- Higher temperatures, low humidity, and direct sunlight will speed up curing.
- Allow each coat to dry enough to withstand light vehicular traffic without damage.
- After the final coat, cure for at least 24 hours under good drying conditions.

PACKAGING & AVAILABILITY

5-Gallon plastic pails, 55-gallon drums & 275-gallon plastic totes. Available at all MAC PMP locations.

CAUTIONS

KEEP FROM FREEZING / KEEP OUT OF REACH OF CHILDREN

- Contains refined coal tar which may cause skin irritation.
- Wear gloves and protective clothing during application.
- In case of contact, flush skin or eyes immediately with fresh water.
- If ingested, contact poison control immediately.
- Consult a Safety Data Sheet for details.

WARRANTY & DISCLAIMER

MAC Pavement Maintenance Products offers S.T.A.R. additives that can be used to enhance the longevity, color and performance of various sealers. S.T.A.R. additives are specifically designed for use with MAC 52, Triton, and Micro-Pave. The information provided is based on reliable data but is given without guarantee, as usage conditions are beyond our control. S.T.A.R. Inc shall not be liable for indirect or consequential damages. In the event of a proven defect, S.T.A.R. Inc may replace the product or refund its purchase price at its discretion.

MAC PMP LOCATIONS

1223 Iron St., North Kansas City, MO 64116
 2646 Creve Coeur Dr., St. Louis, MO 63144
 2262 Front St., Pevely, MO 63070
 1912 W. Harry Ct., Wichita, KS 67213



**PAVEMENT
 MAINTENANCE
 PRODUCTS**

816-814-9537
mac-pmp.com